

DH Series

www.fluorel.co.uk/products/recessed.htm

**DH
Series**

10/12



Decorative and
architectural energy
efficient recessed
downlighters

FluorelLighting
Lighting for a brighter future

**Fluorel Lighting is a leading supplier
of innovative energy efficient lighting**

DH Series

Recessed Downlighters

Ideal for a wide variety of applications these downlighters feature cast aluminium bezels and super pure internal reflector



DHM

Quality downlighter with diamond faceted super pure reflector.

| Product Ref | Lamps | Weight |
|-------------|--------------|--------|
| 6.721018L | 1x18w TC-DEL | 1.13kg |
| 6.722018L | 2x18w TC-DEL | 1.13kg |
| 6.721026L | 1x26w TC-DEL | 1.13kg |
| 6.722026L | 2x26w TC-DEL | 1.13kg |

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



DHTM

Quality downlighter with super pure turbo type louvre attachment giving controlled cut off and low glare.

| Product Ref | Lamps | Weight |
|-------------|--------------|--------|
| 6.641018L | 1x18w TC-DEL | 1.36kg |
| 6.642018L | 2x18w TC-DEL | 1.36kg |
| 6.641026L | 1x26w TC-DEL | 1.36kg |
| 6.642026L | 2x26w TC-DEL | 1.36kg |

Dimensions: Ø237mm H.209mm ⌀222mm ▽IP20



DOHM

Quality downlighter with decorative drop opal polycarbonate attachment with chromed conical fixings.

| Product Ref | Lamps | Weight |
|-----------------|--------------|--------|
| 6.721018L/DG008 | 1x18w TC-DEL | 1.36kg |
| 6.722018L/DG008 | 2x18w TC-DEL | 1.36kg |
| 6.721026L/DG008 | 1x26w TC-DEL | 1.36kg |
| 6.722026L/DG008 | 2x26w TC-DEL | 1.36kg |

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



DHWM

Downlighter with wall washer attachment for feature or asymmetric light distribution.

| Product Ref | Lamps | Weight |
|---------------|--------------|--------|
| 6.621018L/WWW | 1x18w TC-DEL | 1.13kg |
| 6.622018L/WWW | 2x18w TC-DEL | 1.13kg |
| 6.621026L/WWW | 1x26w TC-DEL | 1.13kg |
| 6.622026L/WWW | 2x26w TC-DEL | 1.13kg |

Dimensions: Ø192mm H.145mm ⌀176mm ▽IP20



Life

Very shallow closed downlighter with decorative toughened front glass.

| Product Ref | Lamps | Weight |
|-------------|----------------|--------|
| DHLF218HFL | 2 x 18w TC-DEL | 1.5kg |
| DHLF226HFL | 2 x 26w TC-DEL | 1.5kg |

Dimensions: Ø230mm H.125mm ⌀215mm ▽IP20



Splash

Downlighter with etched halo and decorated toughened drop glass attachment. This model is also available in IP54 version.

| Product Ref | Lamps | Weight |
|-----------------|----------------|--------|
| DHSP218HFL | 2 x 18w TC-DEL | 1.7kg |
| DHSP226HFL | 2 x 26w TC-DEL | 1.7kg |
| DHSP218HFL/IP54 | 2 x 18w TC-DEL | 1.7kg |
| DHSP226HFL/IP54 | 2 x 26w TC-DEL | 1.7kg |

Dimensions: \varnothing 230mm H.160mm \otimes 215mm ∇ IP20 or IP54 as indicated



Extra

Shallow Square downlighter with etched toughened front glass.

| Product Ref | Lamps | Weight |
|-------------|----------------|--------|
| DHEX218HFL | 2 x 18w TC-DEL | 2.2kg |
| DHEX226HFL | 2 x 26w TC-DEL | 2.2kg |

Dimensions: 230x230mm H.125mm \otimes 205x205mm ∇ IP20/23



Fox

Square downlighter with etched halo and clear toughened drop glass attachment.

| Product Ref | Lamps | Weight |
|-------------|----------------|--------|
| DHFX218HFL | 2 x 18w TC-DEL | 2.2kg |
| DHFX226HFL | 2 x 26w TC-DEL | 2.2kg |

Dimensions: 247x247mm H.130mm \otimes 205x205mm ∇ IP20



Living

Square downlighter with etched toughened drop glass attachment.

| Product Ref | Lamps | Weight |
|-------------|----------------|--------|
| DHLV218HFL | 2 x 18w TC-DEL | 2.2kg |
| DHLV226HFL | 2 x 26w TC-DEL | 2.2kg |

Dimensions: 247x247mm H.130mm \otimes 205x205mm ∇ IP20



Tekno

Square downlighter with soft curved profile etched toughened drop glass attachment.

| Product Ref | Lamps | Weight |
|-------------|----------------|--------|
| DHTE218HFL | 2 x 18w TC-DEL | 2.2kg |
| DHTE226HFL | 2 x 26w TC-DEL | 2.2kg |

Dimensions: 260x260mm H.110mm \otimes 205x205mm ∇ IP20

DH

Series



- All luminaires are supplied with lamps* and suspension kits.
- Emergency versions are available - suffix /EMG when ordering.
- Self Test emergency versions are available – suffix /STEMG when ordering.
- Please contact Fluorel or see www.fluorel.co.uk for photometric data.
- Fluorel recommend the use of support trays or reinforcement if using downlighters in very soft fibrous ceiling materials.

LongLast™

- 1,200,000 minutes or 2.5 years of continuous light
Rated Average Life for Biax™ LongLast Q/E, D/E and T/E lamps is 20000 hours (switching cycle:11 Hrs ON/1 Hr OFF).
- Energy saving without loss of light output
- Low energy consumption
- LongLast lamp life up to 20x longer than incandescent lamps
- 80% savings over incandescent lamps
- Triple tube ultra compact design
- Reduces operating costs
- Low mercury content

T5WattMiser™

2DWattMiser™

LongLast™

Fluorel Lighting Limited
Designers and manufacturers of luminaires

Fluorel Lighting Ltd, Unit 25 Eldon way,
Hockley, Essex, SS5 4PS
Tel +44(0)8458 643 643 Fax +44(0)20 8506 1792
info@fluorel.co.uk www.fluorel.co.uk

FluorelLighting
Lighting for a brighter future