## E Series LED



www.fluorel.co.uk



- Energy saving / high output LED
- Excellent photometric performance
- IP65 for internal or exterior use
- Vandal resistent enclosure
- Mains and emergency options
- Aluminium base / polycarbonate diffuser



Fluorel Lighting is a leading supplier of innovative energy efficient lighting

## **E Series LED** www.fluorel.co.uk/products/PDFs

The new EJF and EKF LED luminaires provide an attractive but robust solution for providing lighting to walkways, tunnels, storage areas, car parks etc. The enclosures are sealed to IP65 and house a geartray with HF electronic driver and multi-circuit LED board. The polycarbonate lens and halo-effect side band provide excellent photometric performance (1250 luminaire lumens). The robust cast aluminium and polycarbonate enclosure is vandal resistant and provides protection to IP65. Suitable for ambient temperatures of up to 35°C (25°C for emergency versions), the units are ideal for interior and exterior environments.

The EJF and EKF are available with mains only, or switchable maintained operation. All emergency versions provide 3 hour duration as standard from integral high temperature nickel cadmium batteries. Maintained versions can be used for standard switched mains lighting but will automatically provide emergency lighting in the event of a complete loss of normal mains supply.

The luminaires fully comply to the requirements of EN60598.2.22





Surface mount w	hite LEDs
Part number	EKF20LED (add /EMG for emergency)
Light output	1250 lumens (mains)
Supply power	20 Watts
IP Rating	IP65 ta25
Dimensions	300mm (square) x 100mm(h)
Max weight	2.7kg

## Fluorel Lighting Limited Designers and manufacturers of lighting fittings

Unit 25 Eldon Way, Hockley Essex SS5 4AD Tel +44(0)8458 643 643 Fax +44(0)20 8506 1792 info@fluorel.co.uk www.fluorel.co.uk

