

T6 CDC

Recessed Fluorescent Range / Concealed Grid with CAT2



The flagship range of our recessed luminaire is designed to suit today's growing demands of lighting criteria.

Specification

- Injection moulded end cap
- Suitable for 15-25mm exposed T grid ceiling
- Suitable for plasterboard ceiling (see optional extra)
- Powder coated steel cover with louvre
- Injection moulded polycarbonate body
- UV stabilised

Application

- Reception
- Conference Room
- Call Centre
- Circulation Area
- Offices
- Shops



Product Codes

T6CDC155PZ	1 x 55W PLL
T6CDC255PZ	2 x 55W PLL
T6CDC214FZ	2 x 14W T5
T6CDC314FZ	3 x 14W T5
T6CDC414FZ	4 x 14W T5
T6CDC224FZ	2 x 24W T5
T6CDC324FZ	3 x 24W T5
T6CDC424FZ	4 x 24W T5

Add suffix /EM for 3hr Maintained Emergency

Select End Cap From Below

End Cap (Set)

OEM-CDX-ECW White End Cap
OEM-CDX-ECS Chrome End Cap

Optional Extras

OEM-ATT-01 Plasterboard Recessing Kit
T6CDXSB Surface Conversion Box

Dimensions

