

Gilian® 5000

5 Litre Live Flow Programmable Air Sampling Pump



- NiMH Memory-Free Battery**
NiMH battery ends memory problems associated with NiCad batteries. Quick-charge time in under 4 hours.
- Programmable Functionality**

 - Four stage program with repeat cycling
 - Allows scheduled sampling or intermittent duty cycles
 - Programmable delayed start
- EN 1232 Compliant**
Meets European EN 1232 requirements for personalized sampling pump performance in workplace environments.
- Intuitive Operation with Lock-out Feature**
Simple four-button design makes pump easier to understand and operate.
- 30-Day Calibration**
Special flow control circuitry automatically compensates for changes in flow rate, pressure and temperature.
- Live Flow Display**
Large display continuously shows real-time flow, total sample time and total volume sampled.
- Intrinsically Safe Certified**
Certified Intrinsically Safe for use in explosive environments.

Ordering Information

Description	Part Number
Gilian 5000 Pump Kit.....	810-0801-01
Gilian 5000 Pump Starter Kit, with Charger (100-240VAC, 50/60Hz), UK Cord	910-0802-03
Gilian 5000 Pump 5-pack Kit, with Power Pack (100-240VAC, 50/60Hz), UK Cord.....	910-0801-03
Single Station Charger (100-240VAC, 50/60Hz), UK Cord.....	811-0802-03
Five-Unit Power Pack (100-240VAC, 50/60Hz), UK Cord	811-0801-03
Battery Pack.....	783-0007-01
Battery Charging Cover.....	202783
Low Flow Adapter.....	801961

UK SALES & SERVICE CENTRE



Pioneer Road Faringdon Oxfordshire SN7 7BU
 Tel: 01367 246960 Fax: 01367 243200
 info@shawcity.co.uk www.shawcity.co.uk

Product Specifications

PERFORMANCE

Flow Range.....	20 - 5000 cc/min (Total*), 1000 - 5000 cc/min (High Flow); 20-750 cc/min (Low Flow*) *with low flow constant pressure adapter
Constant Flow Control	± 5% of set flow at 1000-5000 cc/min
Flow Compensation.....	5000cc up to 24" H ₂ O back pressure 4000cc up to 30" H ₂ O back pressure 3000cc up to 50" H ₂ O back pressure 2000cc up to 60" H ₂ O back pressure 1000cc up to 70" H ₂ O back pressure
Run Time	8 hour minimum
Flow Fault	If flow changes exceed 5% within back pressure specifications, fault icon appears. If fault exceeds 30 seconds, pump shuts down. Pump attempts to restart every 3 minutes for up to 1 hour.

ENVIRONMENTAL

Temperature Ranges	
Operating	32°F to 113°F (0°C to 45°C)
Storage	-4°F to 113°F (-20°C to 45°C)
Charging	41°F to 104°F (5°C to 40°C)
Humidity Ranges	
Operating	5-85 %RH, non-condensing
Storage	5-98 %RH, non-condensing

GENERAL

Display.....	Flow Rate, Total Sample Time, Total Volume Sampled
Controls.....	POWER/ENTER, SET/CAL, ▲/CLEAR, ▼/RUN/STOP
Indicators	Green LED ("Normal Operation")
Icons (LCD).....	Battery Indicator, Hold, Fault, Set, Pump
Dimensions	3.2W x 5.4H x 2.3D inches 8.2W x 13.7H x 5.8D cm
Weight.....	20.5 oz. (580 g)

ELECTRICAL

Battery Pack.....	Removable, Rechargeable Nickel-Metal-Hydride
Battery Level Indicator.....	Icon displays Full, Mid, & Low levels
Interface Connectors.....	Charging Jack
Charging Time	Under 4 hours

APPROVALS/PERFORMANCE

EN 1232.....	Type P
Intrinsic Safety	
US/Canada NRTL (FM)....	Class I, Div 1 Groups A, B, C, D; Class II, Div 1, Groups E, F & G; Class III, T4
ATEX	Ex II 1 G Ex ia IIC T4
CE	
Applicable Directives.....	ATEX 94/9/EC EMC 2004/108/EC (RFI) LVD 2006/95/EC