

The **Swingmatic PnG** is ideal for users with limited strength as it opens automatically following an initial push or pull. The PnG can also be opened via the remote control supplied or by other actuators such as push buttons, switches or card readers. The robust and compact PnG is easy to fit onto a range of doors up to 1200mm wide and weighing 120kgs, including fire doors. The PnG requires a 13amp socket or spur nearby to connect into. The PnG utilises the latest encoder technology and is simple to set up using a plug-in hand-held programmer.

- Push or pull the door and the door opens automatically
- Up to date encoded technology
- Manual access in event of power failure
- Battery back up (optional extra)
- Safety protection against over heating, current overload & obstacle encounters
- Attractive slide arm & track
- Remote control as standard
- Wide Choice of Actuators eg pushbuttons, Microwave detectors, Card readers etc.
- Electric lock interface
- Fire alarm interface
- Hand held programmer for easy parameter setting
- Door Leaf width 1200mm weight 120kgs
- Suitable for single leaf & double leaf doors
- Finish silver
- CE Approved

Technical Data-Drive Unit

weight 8kgs

TECHNICAL INFORMATION

- size L480mm x H120mm x D78 mm
- **power consumption** 45w

POWER SUPPLY 240vac

POWER SUPPLY EXTERNAL ACCESSORIES 12vdc 500mA max

Adjustable Parameters

OPENING TIME 3-6 secs CLOSING TIME 3-6 secs HOLD OPEN TIME 0-60 secs Unlocking time for electric lock OPENING ANGLE 60°-120°

OPERATING CYCLE > (unlock) **>** open **>** buffer action & stop **>** hold open **>** close **>** buffer action & stop **>** (lock & seal)

 $\label{eq:Full range of accessories available upon request. For more information please contact:$

TEL & FAX **+44(0)1273 693393** E-MAIL **sales@adcswingmatic.com** Advanced Door Controls Ltd 1c Bonchurch Road Brighton East Sussex BN2 3PJ England